

ioSafe S2



Photo by: Marcia Chodentko

ioSafe S2: Product Highlights

- ioSafe® FloSafe Air Cooled Technology
- Simple Remote Office / SMB Continuity and Disaster Recovery
- Replaces or supplements Tape and Online Backup Strategies
- 2 Hot-swappable SATA hard disks
- Operates up to Industry Standard 40°C
- Fire resistant to 1700°F, 1 hour
- Water resistant: Full Immersion, 30' depth
- Floor Standing Mini Tower
- Rack Mount Capable Design
- Up to 2 TB raw storage capacity
- Removable Electronic Core for Future Upgrades
- After Fire - User Recoverable : reduces Recovery Time Objective (RTO)
- LCD interface
- USB 2.0 interface
- Compatible with Windows, Linux and Macintosh
- Requires no daily user interaction
- Weight: 105 lbs

Email sales@iosafe.com or go to www.iosafe.com

PRELIMINARY : ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE


ioSafe[®]
disaster proof hardware



ioSafe S2: USB/RAID1

Product Specifications

Operational Details:

1. Provides RAID Level 1 for data redundancy
2. Hosts two 3.5" drives
3. Requires no additional software or controller card to operate.
4. Hot swappable disks
5. LCD display for system and hard drive status
6. LED read/write indicators and audible alarm
7. Forced air cooling.
8. Multi-platform compatibility: Windows, Mac and Linux
9. USB 2.0 Interface
10. SNMP Monitoring and Traps

Disaster & Security Specifications:

1. Fire protection – 1700°F, 1 hour
2. Tested per UL, FCC and CE Standards
3. Flood / submersion protection – to 30 feet water depth
4. Proven Data Protection and Recovery. Certified Independent Test Facility.
5. User recoverable data after fire
6. Physical Theft protection
7. Cable lock optional
8. Earthquake / crush protection

Support:

1. 12/7/365 ioSafe Disaster Response Team Support and Data Recovery (included with purchase)
2. \$10,000 Data Extraction Guarantee (\$5000 per disk) and free replacement unit with recovered data.
3. 3 Year Disaster Protection Plan* included with purchase. 5 Year Protection Plan optional.
4. Ongoing Maintenance plans available.

Backup Options:

1. Backup Software Independent:
Works with any disk backup program

Electrical:

1. Electrical – AC input
2. Voltage: 80 ~ 264 VAC at 50/60 HZ
3. Typical Power Consumption: < 75W with 2 HDD

Operating Environmental:

1. Operating: 0-40° C (104°F)
2. Non-operating: 0-1700°F, 1 hour
3. Operating Humidity: 20% - 80% (non-condensing)
4. Non-operating Humidity: 100%, Full water immersion, 30 feet.

Physical:

1. Size: 16"W x 6.75"H x 23"L
2. Rack Mount Capable
3. Weight: 105 lbs
4. User removable core electronics for future upgrades